

Cleaning Guide

ROLLER SHUTTERS, ALUMINIUM PLANTATION SHUTTERS, EXTERNAL VENETIAN BLINDS

To maintain the performance and appearance of your CW Shutters, regular cleaning and care is essential. Follow the steps below to ensure your shutters last for years to come:

General Care Tips

1. Clean Regularly with Mild Soapy Water

Use a soft, non-abrasive cloth or sponge and mild soapy water to wipe down the surfaces of your shutters. This applies to all CW shutter types.

2. Remove Harmful Residue Promptly

For external shutters, it's important to remove:

- Salt residue
- Tree gum and tannins
- Other environmental deposits

3. Dust Regularly

- In coastal or high-salinity areas, clean shutters every 2–4 weeks to prevent salt-related corrosion on metal surfaces.

4. Avoid Water Ingress into the Pelmet

When cleaning, ensure water does not enter the pelmet, especially if your shutters are motorised. Moisture can damage the internal motor and electrical components.

5. Do Not Use Grease or Regular Lubricants

- Avoid using standard lubricants like grease or oil, as these attract dust and grit, causing unnecessary wear.

✓ **Recommended:** Use a dry silicone lubricant for smooth operation without buildup.

With consistent care and proper maintenance, your CW Shutters will continue to look great and function efficiently for many years.

